

# FLOORON

**Easy,  
fast,  
safe**

- for welding thermoplastic floors and linoleum
- digital display of speed, temperature and air flow
- automatic drive start system
- optical wall switch with backlash make sure the machine stops at the wall and the floor is not burned
- integrated dereller system



Because more air flow high welding speed.  
Optical wall switch with backlash make sure  
the machine stops at the wall.



**Technical data**

Voltage	V	230
Frequency	Hz	50/60
Power consumption	W	2300/2900
Temperature	°C (°F)	20–620 68–1148
Speed	m/min (feet/min)	0,5–12 (1,6–39)
Air flow max. (20 °C)	l/min	500
Air flow	%	50–100 variable
Noise level	dB	50
Size (l x w x h)	mm	410 x 260 x 200
Weight	kg	11,5 with 5 m cord
Protection class I		⊕



optical wall switch with backlash

Available on request  
in 120 V.

**BAK**  
[www.bak-ag.com](http://www.bak-ag.com)

BAK Thermoplastic  
Welding Technology AG  
Birkenweg 3  
6056 Kägiswil/Switzerland

E-Mail [info@bak-ag.com](mailto:info@bak-ag.com)  
Telefon +41 (0)41 661 22 50  
Fax +41 (0)41 661 22 51

Thermal Aire Technologies, Inc.

[www.ThermalAireTech.com](http://www.ThermalAireTech.com)  
800-232-3208

Authorized BAK Distributor